



OPTIONAL EXTRAS

Motorized Pulley 400L, 400M & 400H

Specification	Availability	
Total stainless steel option AISI 304 range	TS9N with regreasable labyrinth seals	x
Total stainless steel option AISI 304 range	TS10N with standard seals	x
Semi-rust free option	TS11N with regreasable labyrinth seals	x
Semi-rust free option	TS12N with standard seals	x
Regreasable labyrinth seals		x
Food grade oil & grease - FDA & USDA recognized		x
Dust explosion proof Motorized Pulleys - ATEX 95 - Zone 22 - for applications handling of dusty grain etc. According to European Directive 94/9/EC.		o
Total acid resistant stainless steel option - AISI 316 range		x
Black rubber lagging - Standard specifications (See page 82-83.)		
5/16" full diamond lagging - Hardness 60 ±5 Shore A ≤ 15 HP		o
5/16" partial diamond lagging - Hardness 60 ±5 Shore A 20 HP		o
White smooth rubber lagging (FDA listed) - Oil, fat & grease resistant		o
Special lagging (e.g. hot vulcanized)		o
Electromagnetic brake	Min RL increases by 3.94"	x
Mechanical backstop	Min. RL increases by 1.97" for 400L	x
	Min. RL = 29.53" for 400M	x
	Min. RL = 31.50" for 400H	x
Modified for vertical mounting		o
Modified for mounting between 5° and 90°		o
Insulation class F with standard oil: (Allowable ambient temperature -13°F/+104°F)		x
Insulation class H with synthetic oil: (Allowable ambient temperature -13°F/+120°F)		Std.
Special motors for applications with no belt contact		o
Low noise drives for noise sensitive areas		x
Parallel shell (i.e. no crown)		x
Thermal protector		Std.
IP66/67 Standard yellow powder coated aluminum terminal box	400L	Std.
IP66/67 Optional gray powder coated aluminum terminal box (food grade approved)	400L	x
IP66/67 Standard yellow powder coated cast iron terminal box	400M & 400H	Std.
Straight or elbow connector with standard power cord	400L ≤ 5.5 HP only	x
Straight connector with screened power cord (See page 86 for VFD precautions)	400L ≤ 5.5 HP only	x
Straight connector with power cord (Stainless steel in AISI 304 range)	400L ≤ 5.5 HP only	x
Voltage: single voltage (460) stator (Y winding) wired for 460v/3ph/60 Hz at terminal box		Std
single voltage (230) stator (Y winding) wired for 230v/3ph/60 Hz at terminal box		x
Special voltage motors		x
CSA approved motors		x

x = Optional extras

o = An option with certain limitations. Please refer to Technical precautions pages 78-98.

Std. = Fitted as standard