



OPTIONAL EXTRAS

Motorized Pulley 500L, 500M & 500H

Specification		Availability
Semi-rust-free option	TS11 with regreasable labyrinth seals	x
Semi-rust-free option	TS12 with standard seals	x
Regreasable labyrinth seals		x
Dust explosion proof Motorized Pulleys - ATEX 95 - Zone 22 - for applications handling of dusty grain etc. According to European Directive 94/9/EC.		o
Standard black rubber lagging (See page 82-83.)		
3/8" full smooth lagging - Hardness 60 ±5 Shore A		o
3/8" full diamond lagging - Hardness 60 ±5 Shore A		o
3/8" partial smooth lagging - Hardness 60 ±5 Shore A		o
Special lagging - e.g. hot vulcanized, partial, and ceramic (See page 80.)		o
Internal electromagnetic brake (not available in 500H)	Min. RL increases by 3.94" for 500L and 500M	x
External brake shaft (for mechanical brake by others)	Only available in 500H	x
Mechanical backstop	Min. RL = 29.53" for 500L	x
	Min. RL = 31.50" for 500M	x
	Min. RL = 29.53" for 500H	x
Insulation class F with standard oil: (allowable ambient temperature: -13°F/+104°F)		x
Insulation class H with synthetic oil: (allowable ambient temperature: -13°F/+120°F)		Std.
Parallel shell		x
Thermal protector		Std.
Voltage: Single voltage (460) stator (Y winding) wired for 460v/3ph/60 Hz at terminal box		Std.
IP66/67 Standard yellow powder coated cast iron terminal box		Std.
Special voltage motors		x
CSA approved motors		x

x = Optional extras

o = An option with certain limitations. Please refer to Technical precautions pages 78-98.

Std. = Fitted as standard