



Motorized Pulley 630M & 630H, Ø 24.80 in. (630 mm)

Our 24.80" diameter Motorized Pulley range offers two different performance levels for BULK applications:

- M for Medium duty
- H for Heavy duty

It is important to note the product differences and choose the appropriate pulley based on estimated belt tension (radial load.) See page 80. The actual radial load must be less than the maximum allowable radial load shown in this catalog.

Be aware of increased belt tensions required to drive multi-ply thick heavy belts and/or larger belt widths.

If the 24.80" diameter model is not strong enough to resist estimated belt tension, then select 31.50" diameter model.

M for Medium duty

A solid 2-stage gearbox enables the 630M to handle irregular loadings in harsh operating conditions. 630M uses motor and gearbox from 500H. Note that 630M outer dimensions do not match 630H

H for Heavy duty

630H has stronger internal components with gearbox, shaft, and bearings designed for tough, irregular, and extreme operating conditions.

STANDARD SPECIFICATION of Motorized Pulley

- Crowned mild steel 24.80" diameter steel shell painted yellow at a minimum thickness of 2.4 mils
- Bolted powder coated cast iron bearing housings and covers, all painted yellow at a minimum thickness of 2.4 mils
- Mild steel shafts with nitrided shaft sleeves.
- Shaft sealing system - degree of protection IP66/67 (EN60034-5.) See page 37.
- Cast iron terminal box for painted yellow at min.thickness of 2.4 mils
- 3-phase induction motors with thermal protector
- Voltage: All common voltages available. Please specify.
- Motor winding insulation Class H
- Dynamically balanced rotor
- Two oil plugs each fitted with a magnet to filter the oil
- Yellow painted mounting brackets (AL & ALO) included with pulley
- Oil change recommended every 50,000 operational hours for synthetic oil (or 20,000 operational hours for mineral oil.)
- Minimum RL. Refer to pages 63
- Maximum RL - Please inquire
- Non standard RL's available
- To be used in horizontal positions ±5 degree only

Please note:

- **Noise-sensitive Areas:** High speed 2-pole motors can cause higher noise levels and are not recommended for noise-sensitive areas
- **Technical Precautions for Design, Installation, and Maintenance:** pages 78-98
- **Environmental Considerations:** page 76-77
- **Optional Extras:** page 61 and back cover
- **Electrical Connection Diagrams:** pages 92-98.

SEMI-RUST-FREE options

TS11

- Painted mild steel shell at minimum thickness of 4.7 mils
- Painted cast iron end housings at minimum thickness of 4.7 mils
- Stainless steel bearing covers with labyrinth grooves - AISI 304 range
- Nitrided shaft sleeves
- Zinc-plated oil plugs - each with magnet
- Zinc-plated exterior bolts
- Shaft sealing system - degree of protection P66/67 (EN60034-5) See pg 37.
- Painted terminal box at minimum thickness of 4.7 mils
- Nickel plated mounting brackets with labyrinth grooves

TS12

- As TS11, but without regreasable seals.
- Covers - standard

Please note:

- FDA & USDA food grade recognized oil and grease are not included in TS11 & TS12, but available on request.

Please specify required TS number when ordering Stainless Steel options.