



OPTIONAL EXTRAS

Motorized Pulley 800M, 800H, & 800HD

Specification	Availability
Semi-rust-free option TS11 with regreasable labyrinth seals	x
Semi-rust-free option TS12 with standard seals	x
Regreasable labyrinth seals	x
Dust explosion proof Motorized Pulleys - ATEX 95 - Zone 22 - for applications handling of dusty grain etc. According to European Directive 94/9/EC.	x
Standard black rubber lagging (See pages 82-83.)	
3/8" full smooth lagging - Hardness 60 ±5 Shore A	o
3/8" full diamond lagging - Hardness 60 ±5 Shore A	o
3/8" partial smooth lagging - Hardness 60 ±5 Shore A	o
Special lagging - e.g. hot vulcanized, partial, and ceramic (See pages 82-83.)	o
External brake shaft (for mechanical brake by others)	x
Mechanical backstop	
Min. RL = 37.40" for 800M	x
Min. RL = 45.28" for 800H ≤ 100 HP	x
Min. RL = 55.12" for 800H > 100 HP	x
Insulation class F with standard oil: (allowable ambient temperature: -13 F/+104 F)	x
Insulation class H with synthetic oil: (allowable ambient temperature: -13 F/+120 F)	Std.
Parallel shell	x
Thermal protector	Std.
Voltage: Single voltage (460) stator (Y winding) wired for 460v/3ph/60 Hz at terminal box	Std.
IP66/67 Standard yellow powder coated cast iron terminal box	Std.
Special voltage motors	x
CSA approved motors	x

x = Optional extras

o = An option with certain limitations. Please refer to Technical precautions pages 78-98.

Std. = Fitted as standard