



# Motorized Pulley 165LS

Ø 6.50 in. (165 mm), with helical steel gearbox

## Product description

This Motorized Pulley is ideal for longer or inclined heavy duty unit handling and food processing conveyors.

## Characteristics

- Asynchronous 3 phase AC induction motor
- Integral motor protection
- Hardened steel helical gearbox
- Low noise operation
- Reversible operation

## Applications

- Package handling conveyors with frequent use
- Logistics applications
- Dynamic weighing equipment
- Telescopic conveyors
- Agricultural conveyors
- Food processing equipment
- Positive drive and modular belt conveyors
- Dry, humid and wash down applications

Technical data	
Type of Motor	Asynchronous squirrel-cage, IEC 34 (VDE 0530)
Insulation class of motor windings	Class F, IEC 34 (VDE 0530)
Available power supplies*	115v/1ph/60Hz, 230v/1ph/60Hz, 230v/3ph/60Hz, 460v/3ph/60Hz
Seal protection rating (standard)	IP66
Seal protection rating (optional)	IP69
Thermal protection	Bimetallic contact
Allowable ambient temperature, 3-phase motor	-13° F to +104° F
Max. Roller length (RL)	70.87 in

\* Other power supply voltages and frequencies are available.



# Motorized Pulley 165LS

Ø 6.50 in. (165 mm), with helical steel gearbox



## Materials

Component	Version	Aluminum	Steel	Stainless steel
Shell	Crowned	-	Std	Opt
	Cylindrical	-	Std	Opt
	Cylindrical with key (for sprockets)	-	Opt	Opt
	Special profiles	-	Opt	Opt
End housing	Standard	Std	-	Opt
Shaft	Standard	-	Std	Opt
	Cross-drilled and threaded, M6	-	Opt	Opt
Electrical termination	Power cord with straight ss connector	-	-	Std
	Power cord with elbow ss connector	-	-	Std
	Terminal box	Std	-	Opt

## Options

- Rubber lagging for standard belts
- Profiled lagging for positive drive belts
- Profiled ss shells for positive drive belts
- Mechanical backstop
- Special smooth stainless steel end housings, slotted screw oil plugs, Viton® shaft seals and PTFE deflection seals (option TS8N) for IP69 sealing.
- Special smooth stainless steel end housings, slotted screw oil plugs, labyrinth seals (option TS7N) for IP66 sealing.
- Electromagnetic brake
- Rectifier
- Encoder
- Food grade oil (EU, FDA and USDA)
- Non-horizontal mounting (more than ± 5°)

## Power Cord Specifications

- Standard, shielded, 10 feet long
- Other types & lengths available upon request