



OPTIONAL EXTRAS

Motorized Pulley 138E

Specification	Availability
Total stainless steel option AISI 304 range	TS7N with regreasable labyrinth seals
Food grade oil & grease - FDA & USDA recognized	
Dust explosion proof Motorized Pulleys - ATEX 95 - Zone 22 - for applications handling dusty grain etc. According to European Directive 94/9/EC.	
Total acid resistant stainless steel option - AISI 316	
Black rubber lagging - Standard specifications (See page 82-83.) 1/8" smooth lagging - Hardness 60 ±5 Shore A	
White smooth rubber lagging (FDA). Oil, fat & grease resistant	
Special lagging (e.g. hot vulcanized)	
Electromagnetic brake	Min. RL increases by 1.97"
Mechanical backstop	Min. RL does not increase with backstop option
Modified for vertical mounting	
Modified for mounting between 5° and 90° (e.g. for magnetic separators)	
Insulation class F with standard oil: (Allowable ambient temperature: -13°F/+104°F)	
Insulation class H with synthetic oil: (Allowable ambient temperature: -13°F/+120°F)	
Special motors for applications with no belt contact	
Low noise drives for noise sensitive areas	
Parallel shell	
Thermal protector	
IP66/67 Compact unpainted aluminum terminal box	
IP66/67 Compact stainless steel terminal box- AISI 304 or 316 range	
Straight or elbow connector with standard power cord	
Straight connector with screened power cord	(See page 86 for VFD precautions)
Straight connector with standard power cord	(Stainless steel in AISI 304 range)
Voltage: single voltage (460) stator (Y winding) wired for 460v/3ph/60 Hz at terminal box	
single voltage (230) stator (Y winding) wired for 230v/3ph/60 Hz at terminal box	
2 speed motors	
Special voltage motors	
Single phase motors	
CSA approved motors	

x = Optional extra's

o = An option with certain limitations. Please refer to Technical precautions pages 78-98.

Std. = Fitted as standard