

Mounting Brackets for Motorized Pulley and Idler



Mounting brackets: From left to right, 6YA0U (stainless steel for model 165LS), S2YAKA (stainless steel for model 138LS), S1MB03 (aluminum for model 113LS), and S0MB03 (aluminum for model 80LS)

Dimensions, materials, and weights for Mounting Brackets

Motorized Pulley	Standard Matl./ Part Number	Optional Matl./ Part Number	D [in]	F [in]	I [in]	K [in]	S [in]	T [in]	V [in]	W1 [in]	X [in]	X1 [in]	Z [in]	Z1 [in]	Thread	Weight [lbs]
80LS	Aluminum S0MB03	Stainless steel S0MB-US00SS	0.79	0.55	2.24	1.50	0.26	0.35	0.47	0.39	2.83	4.06	1.38	2.17	M6	0.3/0.5
113LS	Aluminum S1MB03	Stainless steel S1MB-US00SS	0.98	0.79	3.35	2.17	0.33	0.43	0.59	0.79	4.33	5.91	1.65	2.60	M6	1.1/2.0
138LS	Cast iron black paint S2YAKL	Stainless steel S2YAKA	1.18	0.79	3.39	2.24	0.43	0.67	0.47	0.94	4.33	7.09	1.75	2.83	M8	3.1
165LS	Cast iron black paint 6YA0K	Stainless steel 6YA0U	1.57	1.18	3.31	2.44	0.55	0.79	0.87	1.57	4.33	7.48	1.97	3.27	M8	4.4

