



Ordering* Information: Rulmeca Drum Motors

Email: sales-us@rulmeca.com

Fax: 910-794-9296

Contact Person _____ Date _____ Ref# _____

Company _____

Address _____

Phone _____ Fax _____ Email _____

Diameter (in)		Roller Length (in)		Belt Speed (fpm)		Lagging Material		Type of Mounting Brackets	
<input type="checkbox"/>	3.15	<input type="checkbox"/>	11.81	<input type="checkbox"/>	10	<input type="checkbox"/>	Blue rubber	<input type="checkbox"/>	aluminum
<input type="checkbox"/>	4.50	<input type="checkbox"/>	12.60	<input type="checkbox"/>	12	<input type="checkbox"/>	White rubber	<input type="checkbox"/>	stainless steel
<input type="checkbox"/>	5.45	<input type="checkbox"/>	13.78	<input type="checkbox"/>	14	<input type="checkbox"/>	Black rubber	<input type="checkbox"/>	cast iron
<input type="checkbox"/>	6.49	<input type="checkbox"/>	15.75	<input type="checkbox"/>	16	<input type="checkbox"/>	None	Type of Holdback	
Power (HP)		<input type="checkbox"/>	17.72	<input type="checkbox"/>	18	Lagging Profile			
		<input type="checkbox"/>	19.69	<input type="checkbox"/>	20	<input type="checkbox"/>	Smooth	<input type="checkbox"/>	mech. backstop, clockwise
		<input type="checkbox"/>	21.65	<input type="checkbox"/>	24	<input type="checkbox"/>	Profiled	<input type="checkbox"/>	mech. backstop, counterclockwise
		<input type="checkbox"/>	23.62	<input type="checkbox"/>	26	Lagging Thickness		Type of Seals	
		<input type="checkbox"/>	25.59	<input type="checkbox"/>	30				
		<input type="checkbox"/>	27.56	<input type="checkbox"/>	38	<input type="checkbox"/>	1/8 inch	<input type="checkbox"/>	standard
		<input type="checkbox"/>	29.53	<input type="checkbox"/>	48	<input type="checkbox"/>	1/4 inch	<input type="checkbox"/>	IP69
		<input type="checkbox"/>	31.50	<input type="checkbox"/>	60	<input type="checkbox"/>	1/2 inch	<input type="checkbox"/>	regreasable
		<input type="checkbox"/>	33.46	<input type="checkbox"/>	76	Termination (select one)		Material & Surface Finish	
		<input type="checkbox"/>	35.43	<input type="checkbox"/>	96	<input type="checkbox"/>	compact box, AL		
		<input type="checkbox"/>	37.40	<input type="checkbox"/>	120	<input type="checkbox"/>	compact box, SS	<input type="checkbox"/>	stan. mild steel & aluminum
		<input type="checkbox"/>	39.37	<input type="checkbox"/>	150	<input type="checkbox"/>	power cord, elbow connector	<input type="checkbox"/>	total stainless steel
		<input type="checkbox"/>	41.34	<input type="checkbox"/>	192	<input type="checkbox"/>	power cord, straight connector	<input type="checkbox"/>	semi-rust free
		<input type="checkbox"/>	43.31	<input type="checkbox"/>	240	Power cord (if applicable)		Other Special Options	
		<input type="checkbox"/>	45.28	<input type="checkbox"/>	300	<input type="checkbox"/>	10 ft, standard insulation		
		<input type="checkbox"/>	47.24	<input type="checkbox"/>	384	<input type="checkbox"/>	10 ft, screened	<input type="checkbox"/>	vertical shaft
		<input type="checkbox"/>	49.21	<input type="checkbox"/>	480	Type of Oil		<input type="checkbox"/>	inclined shaft
		<input type="checkbox"/>	51.18	<input type="checkbox"/>	600	<input type="checkbox"/>	mineral	<input type="checkbox"/>	encoder (SKF)
		<input type="checkbox"/>	53.15	<input type="checkbox"/>	768	<input type="checkbox"/>	synthetic	<input type="checkbox"/>	encoder (RLS)
		<input type="checkbox"/>	55.12	Voltage		<input type="checkbox"/>	food grade	<input type="checkbox"/>	low noise
		<input type="checkbox"/>	57.09	<input type="checkbox"/>	115v	Motor Insulation		<input type="checkbox"/>	special certification (please specify)
		<input type="checkbox"/>	59.06	<input type="checkbox"/>	208v	<input type="checkbox"/>	class F	<input type="checkbox"/>	special shell (attach drawing)
		<input type="checkbox"/>	61.02	<input type="checkbox"/>	230v	<input type="checkbox"/>	class H	<input type="checkbox"/>	special end housing (attach drawing)
		<input type="checkbox"/>	62.99	<input type="checkbox"/>	230v	Type of Crown		<input type="checkbox"/>	special shaft (attach drawing)
		<input type="checkbox"/>	64.96	<input type="checkbox"/>	380v	<input type="checkbox"/>	center crown	<input type="checkbox"/>	special key requirements (attach drawing)
		<input type="checkbox"/>	66.93	<input type="checkbox"/>	460v	<input type="checkbox"/>	trapezoidal crown	Center Groove Dimensions (if applicable)	
		<input type="checkbox"/>	68.90	<input type="checkbox"/>	575v	<input type="checkbox"/>	no crown		
		<input type="checkbox"/>	70.87	Phase & Frequency				Top _____ (in.)	
		<input type="checkbox"/>	72.83	<input type="checkbox"/>	3ph/60Hz			Bottom _____ (in.)	
		<input type="checkbox"/>	74.80	<input type="checkbox"/>	3ph/50Hz			Depth _____ (in.)	
		<input type="checkbox"/>	76.77	<input type="checkbox"/>	1ph/60Hz				
		<input type="checkbox"/>	78.74	<input type="checkbox"/>	1ph/60Hz				
		<input type="checkbox"/>	Other	<input type="checkbox"/>	1ph/50Hz				

Quantity: _____ Drum Motors

Special Comments: _____

* Note: This form displays all powers, speeds, and options available in small drum motors from Rulmeca. Some combinations are unavailable (e.g. 3 HP is not available in 4.5 inch diameter).