

**ORDERING\* INFORMATION:**  
**Rulmeca Drum Motors**

**Email: sales-us@rulmeca.com**  
**Fax: 910-794-9296**



Contact Person \_\_\_\_\_ Date \_\_\_\_\_ Ref# \_\_\_\_\_  
 Company \_\_\_\_\_  
 Address \_\_\_\_\_  
 Phone \_\_\_\_\_ Fax \_\_\_\_\_ Email \_\_\_\_\_

Diameter (in)		Roller Length (in)		Belt Speed (fpm)		Lagging Material		Type of Mounting Brackets		
<input type="checkbox"/>	3.15	<input type="checkbox"/>	11.81	<input type="checkbox"/>	10	<input type="checkbox"/>	Blue rubber	<input type="checkbox"/>	aluminum	
<input type="checkbox"/>	4.50	<input type="checkbox"/>	12.60	<input type="checkbox"/>	12	<input type="checkbox"/>	White rubber	<input type="checkbox"/>	stainless steel	
<input type="checkbox"/>	5.45	<input type="checkbox"/>	13.78	<input type="checkbox"/>	14	<input type="checkbox"/>	Black rubber	<input type="checkbox"/>	cast iron	
<input type="checkbox"/>	6.49	<input type="checkbox"/>	15.75	<input type="checkbox"/>	16	<input type="checkbox"/>	None	<b>Type of Holdback</b>		
<b>Power (HP)</b>		<input type="checkbox"/>	17.72	<input type="checkbox"/>	18	<b>Lagging Profile</b>				<input type="checkbox"/>
		<input type="checkbox"/>	19.69	<input type="checkbox"/>	20			<input type="checkbox"/>	mech, backstop, counterclockwise	
<input type="checkbox"/>	0.03	<input type="checkbox"/>	21.65	<input type="checkbox"/>	24	<input type="checkbox"/>	Smooth	<b>Type of Seals</b>		
<input type="checkbox"/>	0.05	<input type="checkbox"/>	23.62	<input type="checkbox"/>	26	<input type="checkbox"/>	Profiled			<input type="checkbox"/>
<input type="checkbox"/>	0.08	<input type="checkbox"/>	25.59	<input type="checkbox"/>	30	<b>Lagging Thickness</b>		<b>Type of Seals</b>		
<input type="checkbox"/>	0.09	<input type="checkbox"/>	27.56	<input type="checkbox"/>	38					<input type="checkbox"/>
<input type="checkbox"/>	0.10	<input type="checkbox"/>	29.53	<input type="checkbox"/>	48	<input type="checkbox"/>	1/4 inch	<input type="checkbox"/>	IP69	
<input type="checkbox"/>	0.11	<input type="checkbox"/>	31.50	<input type="checkbox"/>	60	<input type="checkbox"/>	1/2 inch	<input type="checkbox"/>	regreasable	
<input type="checkbox"/>	0.12	<input type="checkbox"/>	33.46	<input type="checkbox"/>	76	<b>Termination (select one)</b>		<b>Material &amp; Surface Finish</b>		
<input type="checkbox"/>	0.13	<input type="checkbox"/>	35.43	<input type="checkbox"/>	96					<input type="checkbox"/>
<input type="checkbox"/>	0.15	<input type="checkbox"/>	37.40	<input type="checkbox"/>	120	<input type="checkbox"/>	compact box, SS	<input type="checkbox"/>	total stainless steel	
<input type="checkbox"/>	0.16	<input type="checkbox"/>	39.37	<input type="checkbox"/>	150	<input type="checkbox"/>	power cord, elbow connector	<input type="checkbox"/>	semi-rust free	
<input type="checkbox"/>	0.20	<input type="checkbox"/>	41.34	<input type="checkbox"/>	192	<input type="checkbox"/>	power cord, straight connector	<b>Other Special Options</b>		
<input type="checkbox"/>	0.24	<input type="checkbox"/>	43.31	<input type="checkbox"/>	240	<b>Power cord (if applicable)</b>				<input type="checkbox"/>
<input type="checkbox"/>	0.25	<input type="checkbox"/>	45.28	<input type="checkbox"/>	300			<input type="checkbox"/>	10 ft, standard insulation	<input type="checkbox"/>
<input type="checkbox"/>	0.33	<input type="checkbox"/>	47.24	<input type="checkbox"/>	384	<input type="checkbox"/>	10 ft, screened	<input type="checkbox"/>	encoder (SKF)	
<input type="checkbox"/>	0.40	<input type="checkbox"/>	49.21	<input type="checkbox"/>	480	<b>Type of Oil</b>		<input type="checkbox"/>	encoder (RLS)	
<input type="checkbox"/>	0.50	<input type="checkbox"/>	51.18	<input type="checkbox"/>	600			<input type="checkbox"/>	mineral	<input type="checkbox"/>
<input type="checkbox"/>	0.75	<input type="checkbox"/>	53.15	<input type="checkbox"/>	768	<b>Motor Insulation</b>		<input type="checkbox"/>	special certification (please specify)	
<input type="checkbox"/>	1.00	<input type="checkbox"/>	55.12	<b>Voltage</b>				<input type="checkbox"/>	synthetic	<input type="checkbox"/>
<input type="checkbox"/>	1.33	<input type="checkbox"/>	57.09			<input type="checkbox"/>	115v	<input type="checkbox"/>	food grade	<input type="checkbox"/>
<input type="checkbox"/>	1.50	<input type="checkbox"/>	59.06	<input type="checkbox"/>	208v	<b>Type of Crown</b>		<input type="checkbox"/>	special shaft (attach drawing)	
<input type="checkbox"/>	2.00	<input type="checkbox"/>	61.02	<input type="checkbox"/>	230v			<input type="checkbox"/>	center crown	<input type="checkbox"/>
<input type="checkbox"/>	3.00	<input type="checkbox"/>	62.99	<input type="checkbox"/>	240v	<b>Phase &amp; Frequency</b>		<b>Center Groove Dimensions (if applicable)</b>		
<b>Quantity: _____ Motorized Pulleys</b>		<input type="checkbox"/>	64.96	<input type="checkbox"/>	380v					<input type="checkbox"/>
		<input type="checkbox"/>	66.93	<input type="checkbox"/>	460v	<input type="checkbox"/>	class H	Bottom _____ (in.)		
		<input type="checkbox"/>	68.90	<input type="checkbox"/>	575v	<b>Type of Crown</b>		<input type="checkbox"/>	center crown	Depth _____ (in.)
		<input type="checkbox"/>	70.87	<input type="checkbox"/>	70.87			<input type="checkbox"/>	trapezoidal crown	
		<input type="checkbox"/>	72.83	<input type="checkbox"/>	72.83	<input type="checkbox"/>	3ph/60Hz	<input type="checkbox"/>	no crown	
		<input type="checkbox"/>	74.80	<input type="checkbox"/>	74.80	<input type="checkbox"/>	3ph/50Hz	<b>Special Comments:</b> _____ _____ _____		
<input type="checkbox"/>	76.77	<input type="checkbox"/>	76.77	<input type="checkbox"/>	1ph/60Hz					
<input type="checkbox"/>	78.74	<input type="checkbox"/>	78.74	<input type="checkbox"/>	1ph/50Hz					
<input type="checkbox"/>	Other	<input type="checkbox"/>	Other	<input type="checkbox"/>	Other					

\* Note: This form displays all powers, speeds, and options available in small drum motors from Rulmeca. Some combinations are unavailable (e.g. 3 HP is not available in 4.5 inch diameter.)