



# ORDERING\* INFORMATION

## Motorized Pulleys

Contact Person \_\_\_\_\_ Date \_\_\_\_\_ Ref # \_\_\_\_\_

Company \_\_\_\_\_

Address \_\_\_\_\_

Phone \_\_\_\_\_ Fax \_\_\_\_\_ Email \_\_\_\_\_

Diameter (in)		Roller Length (in)		Belt Speed (fpm)		Lagging Material	Type of Oil
<input type="checkbox"/>	5.45	<input type="checkbox"/>	11.81	<input type="checkbox"/>	10	<input type="checkbox"/> black rubber, diamond pattern	<input type="checkbox"/> standard
<input type="checkbox"/>	6.49	<input type="checkbox"/>	12.60	<input type="checkbox"/>	12	<input type="checkbox"/> black rubber, smooth pattern	<input type="checkbox"/> synthetic
<input type="checkbox"/>	8.50	<input type="checkbox"/>	12.60	<input type="checkbox"/>	14	<input type="checkbox"/> white rubber, smooth pattern	<input type="checkbox"/> food grade
<input type="checkbox"/>	12.64	<input type="checkbox"/>	13.78	<input type="checkbox"/>	18	<input type="checkbox"/> solid ceramic bonded to pulley shell	<b>Motor Insulation</b>
<input type="checkbox"/>	15.91	<input type="checkbox"/>	15.75	<input type="checkbox"/>	24	<input type="checkbox"/> ceramic plates vulc. into rubber	
<input type="checkbox"/>	19.72	<input type="checkbox"/>	17.72	<input type="checkbox"/>	30	<b>Lagging Bond</b>	<input type="checkbox"/> class F (standard) <input type="checkbox"/> class H
<input type="checkbox"/>	24.80	<input type="checkbox"/>	19.69	<input type="checkbox"/>	38		
<input type="checkbox"/>	31.50	<input type="checkbox"/>	21.65	<input type="checkbox"/>	48	<input type="checkbox"/> cold bonded <input type="checkbox"/> hot vulcanized	<b>Type of Crown</b>
<input type="checkbox"/>	40.16	<input type="checkbox"/>	23.62	<input type="checkbox"/>	60		
<b>Power (HP)</b>		<input type="checkbox"/>	25.59	<input type="checkbox"/>	76	<b>Lagging Thickness</b>	<input type="checkbox"/> center crown <input type="checkbox"/> trapezoidal crown <input type="checkbox"/> no crown
		<input type="checkbox"/>	27.56	<input type="checkbox"/>	96		
<input type="checkbox"/>	0.13	<input type="checkbox"/>	29.53	<input type="checkbox"/>	120	<input type="checkbox"/> 1/8 inch <input type="checkbox"/> 1/4 inch <input type="checkbox"/> 5/16 inch <input type="checkbox"/> 3/8 inch <input type="checkbox"/> 1/2 inch	<b>Mounting Brackets</b>
<input type="checkbox"/>	0.15	<input type="checkbox"/>	31.50	<input type="checkbox"/>	150		
<input type="checkbox"/>	0.25	<input type="checkbox"/>	33.46	<input type="checkbox"/>	192	<b>Termination (select one)</b>	<input type="checkbox"/> standard paint <input type="checkbox"/> nickel plated <input type="checkbox"/> none
<input type="checkbox"/>	0.33	<input type="checkbox"/>	35.43	<input type="checkbox"/>	240		
<input type="checkbox"/>	0.50	<input type="checkbox"/>	37.40	<input type="checkbox"/>	300	<input type="checkbox"/> standard box, standard paint <input type="checkbox"/> standard box, food grade paint <input type="checkbox"/> standard box, unpainted <input type="checkbox"/> compact box, unpainted <input type="checkbox"/> compact box, stainless steel <input type="checkbox"/> power cord, elbow connector <input type="checkbox"/> power cord, stan. straight connector <input type="checkbox"/> power cord, SS straight connector	<b>Type of Holdback</b>
<input type="checkbox"/>	0.75	<input type="checkbox"/>	39.37	<input type="checkbox"/>	384		
<input type="checkbox"/>	1.0	<input type="checkbox"/>	41.34	<input type="checkbox"/>	480	<b>Power Cord (if applicable)</b>	<input type="checkbox"/> mech. backstop, clockwise <input type="checkbox"/> mech. backstop, counterclockwise <input type="checkbox"/> internal brake <input type="checkbox"/> external brake shaft
<input type="checkbox"/>	1.5	<input type="checkbox"/>	43.31	<input type="checkbox"/>	600		
<input type="checkbox"/>	2.0	<input type="checkbox"/>	45.28	<input type="checkbox"/>	768	<input type="checkbox"/> 4 ft, standard insulation <input type="checkbox"/> 4 ft, screened <input type="checkbox"/> 10 ft, standard insulation <input type="checkbox"/> 10 ft, screened	<b>Type of Seals</b>
<input type="checkbox"/>	3.0	<input type="checkbox"/>	47.24	<input type="checkbox"/>	960		
<input type="checkbox"/>	4.0	<input type="checkbox"/>	49.21	<input type="checkbox"/>	1064	<b>Phase &amp; Frequency</b>	<input type="checkbox"/> standard <input type="checkbox"/> regreasable
<input type="checkbox"/>	5.5	<input type="checkbox"/>	51.18	<input type="checkbox"/>	1320		
<input type="checkbox"/>	7.5	<input type="checkbox"/>	53.15	<b>Voltage</b>	<input type="checkbox"/>	208v	<b>Material &amp; Surface Finish</b>
<input type="checkbox"/>	10	<input type="checkbox"/>	55.12		<input type="checkbox"/>	230v	
<input type="checkbox"/>	15	<input type="checkbox"/>	57.09	<input type="checkbox"/>	380v	<input type="checkbox"/> mild steel, standard paint <input type="checkbox"/> total stainless steel <input type="checkbox"/> semi-rust free	
<input type="checkbox"/>	20	<input type="checkbox"/>	59.06	<input type="checkbox"/>	460v		
<input type="checkbox"/>	25	<input type="checkbox"/>	61.02	<input type="checkbox"/>	575v	<b>Other Special Options</b>	
<input type="checkbox"/>	30	<input type="checkbox"/>	62.99	<input type="checkbox"/> 3ph/60Hz <input type="checkbox"/> 3ph/50Hz <input type="checkbox"/> 1ph/60Hz <input type="checkbox"/> 1ph/50Hz	<input type="checkbox"/> vertical shaft (see page 91)		
<input type="checkbox"/>	40	<input type="checkbox"/>	64.96		<input type="checkbox"/> inclined shaft (see page 91)	<input type="checkbox"/> CSA approved motor	
<input type="checkbox"/>	50	<input type="checkbox"/>	66.93		<input type="checkbox"/> dust explosion proof (per ATEX 95, Zone 22)		
<input type="checkbox"/>	61	<input type="checkbox"/>	68.90				
<input type="checkbox"/>	75	<input type="checkbox"/>	70.87				
<input type="checkbox"/>	100	<input type="checkbox"/>	72.83				
<input type="checkbox"/>	122	<input type="checkbox"/>	74.80				
<input type="checkbox"/>	150	<input type="checkbox"/>	76.77				
<input type="checkbox"/>	180	<input type="checkbox"/>	78.74				
<input type="checkbox"/>	220	<input type="checkbox"/>	80.71				
<input type="checkbox"/>	270	<input type="checkbox"/>	82.68				
<input type="checkbox"/>	330	<input type="checkbox"/>	84.65				
<b>Quantity</b> _____ <b>Motorized Pulley(s)</b> <b>Special Comments:</b> _____ _____ _____							

\* Note that this form displays all powers, speeds, and options available from Rulmeca. Some combinations are unavailable (e.g. 100 HP is not available in 12.64" diameter.) For interactive ordering sheet go to [www.rulmecacorp.com](http://www.rulmecacorp.com).