



Motorized Pulley 113LP

Ø 4.47 in. (113 mm), planetary gearbox
in polymer or polymer / steel combination

Product description

This Motorized Pulley is the ideal drive for light and medium duty conveyors, for non-continuous use.

Characteristics

- Asynchronous 3 phase or 1 phase AC induction motor
- Integral motor protection
- Planetary gearbox in polymer or polymer / steel combination
- Low noise operation
- Light and distributed weight
- Maintenance free
- Lifetime lubrication
- Reversible operation
- Motorized Pulleys with RL greater than 27.80 inches have reinforced shaft.

Applications

- Small package handling conveyors with high duty cycle
- Transfer conveyors
- Dynamic weighing equipment
- Metal detectors
- Recycling equipment
- Pharmaceutical equipment
- Food processing equipment
- Positive drive and modular belt conveyors
- Dry, humid and wash down applications

Technical data

Type of Motor	Asynchronous squirrel-cage, IEC 34 (VDE 0530)
Insulation class of motor windings	Class F, IEC 34 (VDE 0530)
Available power supplies*	115v/1ph/60Hz, 230v/1ph/60Hz, 230v/3ph/60Hz, 460v/3ph/60Hz
Seal protection rating	IP66
Thermal protection	Bimetallic contact
Allowable ambient temp, 3-ph motor	+41° F to +104° F
Allowable ambient temp, 1-ph motor	+50° F to +104 °F
Max. Roller length (RL)	47.72 in

* Other power supply voltages and frequencies are available.

