



ORDERING* INFORMATION

Motorized Pulleys

Contact Person _____ Date _____ Ref # _____

Company _____

Address _____

Phone _____ Fax _____ Email _____

Diameter (in)		Roller Length (in)		Belt Speed (fpm)		Lagging Material	Type of Oil
<input type="checkbox"/>	5.45	<input type="checkbox"/>	11.81	<input type="checkbox"/>	10	<input type="checkbox"/> black rubber, diamond pattern	<input type="checkbox"/> standard
<input type="checkbox"/>	6.49	<input type="checkbox"/>	12.60	<input type="checkbox"/>	12	<input type="checkbox"/> black rubber, smooth pattern	<input type="checkbox"/> synthetic
<input type="checkbox"/>	8.50	<input type="checkbox"/>	13.78	<input type="checkbox"/>	14	<input type="checkbox"/> white rubber, smooth pattern	<input type="checkbox"/> food grade
<input type="checkbox"/>	12.64	<input type="checkbox"/>	15.75	<input type="checkbox"/>	18	<input type="checkbox"/> solid ceramic bonded to pulley shell	Motor Insulation
<input type="checkbox"/>	15.91	<input type="checkbox"/>	17.72	<input type="checkbox"/>	24	<input type="checkbox"/> ceramic plates vulc. into rubber	
<input type="checkbox"/>	19.72	<input type="checkbox"/>	19.69	<input type="checkbox"/>	30	Lagging Bond	<input type="checkbox"/> class F (standard) <input type="checkbox"/> class H
<input type="checkbox"/>	24.80	<input type="checkbox"/>	21.65	<input type="checkbox"/>	38		
<input type="checkbox"/>	31.50	<input type="checkbox"/>	23.62	<input type="checkbox"/>	48	<input type="checkbox"/> cold bonded	Type of Crown
<input type="checkbox"/>	40.16	<input type="checkbox"/>	25.59	<input type="checkbox"/>	60	<input type="checkbox"/> hot vulcanized	
Power (HP)		<input type="checkbox"/>	27.56	<input type="checkbox"/>	76	Lagging Thickness	<input type="checkbox"/> center crown <input type="checkbox"/> trapezoidal crown <input type="checkbox"/> no crown
<input type="checkbox"/>	0.13	<input type="checkbox"/>	29.53	<input type="checkbox"/>	96		
<input type="checkbox"/>	0.15	<input type="checkbox"/>	31.50	<input type="checkbox"/>	120	Termination (select one)	Type of Holdback
<input type="checkbox"/>	0.25	<input type="checkbox"/>	33.46	<input type="checkbox"/>	150		
<input type="checkbox"/>	0.33	<input type="checkbox"/>	35.43	<input type="checkbox"/>	192	<input type="checkbox"/> standard box, standard paint	<input type="checkbox"/> mech. backstop, clockwise <input type="checkbox"/> mech. backstop, counterclockwise <input type="checkbox"/> internal brake <input type="checkbox"/> external brake shaft
<input type="checkbox"/>	0.50	<input type="checkbox"/>	37.40	<input type="checkbox"/>	240	<input type="checkbox"/> standard box, food grade paint	
<input type="checkbox"/>	0.75	<input type="checkbox"/>	39.37	<input type="checkbox"/>	300	<input type="checkbox"/> standard box, unpainted	Type of Seals
<input type="checkbox"/>	1.0	<input type="checkbox"/>	41.34	<input type="checkbox"/>	384	<input type="checkbox"/> compact box, unpainted	
<input type="checkbox"/>	1.5	<input type="checkbox"/>	43.31	<input type="checkbox"/>	480	<input type="checkbox"/> compact box, stainless steel	Material & Surface Finish
<input type="checkbox"/>	2.0	<input type="checkbox"/>	45.28	<input type="checkbox"/>	600	<input type="checkbox"/> power cord, elbow connector	
<input type="checkbox"/>	3.0	<input type="checkbox"/>	47.24	<input type="checkbox"/>	768	<input type="checkbox"/> power cord, stan. straight connector	<input type="checkbox"/> mild steel, standard paint <input type="checkbox"/> total stainless steel <input type="checkbox"/> semi-rust free
<input type="checkbox"/>	4.0	<input type="checkbox"/>	49.21	<input type="checkbox"/>	960	<input type="checkbox"/> power cord, SS straight connector	
<input type="checkbox"/>	5.5	<input type="checkbox"/>	51.18	<input type="checkbox"/>	1064	Power Cord (if applicable)	<input type="checkbox"/> standard <input type="checkbox"/> regreasable
<input type="checkbox"/>	7.5	<input type="checkbox"/>	53.15	<input type="checkbox"/>	1320		
<input type="checkbox"/>	10	<input type="checkbox"/>	55.12	Voltage		<input type="checkbox"/> 4 ft, standard insulation <input type="checkbox"/> 4 ft, screened <input type="checkbox"/> 10 ft, standard insulation <input type="checkbox"/> 10 ft, screened	Other Special Options
<input type="checkbox"/>	15	<input type="checkbox"/>	57.09	<input type="checkbox"/>	208v		
<input type="checkbox"/>	20	<input type="checkbox"/>	59.06	<input type="checkbox"/>	230v	<input type="checkbox"/> vertical shaft (see page 91) <input type="checkbox"/> inclined shaft (see page 91) <input type="checkbox"/> CSA approved motor <input type="checkbox"/> dust explosion proof (per ATEX 95, Zone 22)	
<input type="checkbox"/>	25	<input type="checkbox"/>	61.02	<input type="checkbox"/>	380v		
<input type="checkbox"/>	30	<input type="checkbox"/>	62.99	<input type="checkbox"/>	460v		
<input type="checkbox"/>	40	<input type="checkbox"/>	64.96	<input type="checkbox"/>	575v		
<input type="checkbox"/>	50	<input type="checkbox"/>	66.93	Phase & Frequency			
<input type="checkbox"/>	61	<input type="checkbox"/>	68.90	<input type="checkbox"/>	3ph/60Hz		
<input type="checkbox"/>	75	<input type="checkbox"/>	70.87	<input type="checkbox"/>	3ph/50Hz		
<input type="checkbox"/>	100	<input type="checkbox"/>	72.83	<input type="checkbox"/>	1ph/60Hz		
<input type="checkbox"/>	122	<input type="checkbox"/>	74.80	<input type="checkbox"/>	1ph/50Hz		
<input type="checkbox"/>	150	<input type="checkbox"/>	76.77	Quantity _____ Motorized Pulley(s)			
<input type="checkbox"/>	180	<input type="checkbox"/>	78.74	Special Comments: _____			
<input type="checkbox"/>	220	<input type="checkbox"/>	80.71	_____			
<input type="checkbox"/>	270	<input type="checkbox"/>	82.68	_____			
<input type="checkbox"/>	330	<input type="checkbox"/>	84.65	_____			
<input type="checkbox"/>		<input type="checkbox"/>	Other				

* Note that this form displays all powers, speeds, and options available from Rulmeca. Some combinations are unavailable (e.g. 100 HP is not available in 12.64" diameter.)