



ORDERING* INFORMATION

Motorized Pulleys

Contact Person _____ Date _____ Ref # _____

Company _____

Address _____

Phone _____ Fax _____ Email _____

Diameter (in)		Roller Length (in)		Belt Speed (fpm)		Lagging Material		Type of Oil	
<input type="checkbox"/>	5.45	<input type="checkbox"/>	11.81	<input type="checkbox"/>	10	<input type="checkbox"/>	black rubber, diamond pattern	<input type="checkbox"/>	standard
<input type="checkbox"/>	6.49	<input type="checkbox"/>	12.60	<input type="checkbox"/>	12	<input type="checkbox"/>	black rubber, smooth pattern	<input type="checkbox"/>	synthetic
<input type="checkbox"/>	8.50	<input type="checkbox"/>	13.78	<input type="checkbox"/>	14	<input type="checkbox"/>	white rubber, smooth pattern	<input type="checkbox"/>	food grade
<input type="checkbox"/>	12.64	<input type="checkbox"/>	15.75	<input type="checkbox"/>	18	<input type="checkbox"/>	solid ceramic bonded to pulley shell	Motor Insulation	
<input type="checkbox"/>	15.91	<input type="checkbox"/>	17.72	<input type="checkbox"/>	24	<input type="checkbox"/>	ceramic plates vulc. into rubber		
<input type="checkbox"/>	19.72	<input type="checkbox"/>	19.69	<input type="checkbox"/>	30	Lagging Bond		<input type="checkbox"/> class F (standard) <input type="checkbox"/> class H	
<input type="checkbox"/>	24.80	<input type="checkbox"/>	21.65	<input type="checkbox"/>	38				
<input type="checkbox"/>	31.50	<input type="checkbox"/>	23.62	<input type="checkbox"/>	48	<input type="checkbox"/>	cold bonded	Type of Crown	
<input type="checkbox"/>	40.16	<input type="checkbox"/>	25.59	<input type="checkbox"/>	60	<input type="checkbox"/>	hot vulcanized		
Power (HP)		<input type="checkbox"/>	27.56	<input type="checkbox"/>	76	Lagging Thickness		<input type="checkbox"/> center crown <input type="checkbox"/> trapezoidal crown <input type="checkbox"/> no crown	
<input type="checkbox"/>	0.13	<input type="checkbox"/>	29.53	<input type="checkbox"/>	96				
<input type="checkbox"/>	0.15	<input type="checkbox"/>	31.50	<input type="checkbox"/>	120	Termination (select one)		<input type="checkbox"/> standard paint <input type="checkbox"/> nickel plated <input type="checkbox"/> none	
<input type="checkbox"/>	0.25	<input type="checkbox"/>	33.46	<input type="checkbox"/>	150				
<input type="checkbox"/>	0.33	<input type="checkbox"/>	35.43	<input type="checkbox"/>	192	<input type="checkbox"/>	1/8 inch	Type of Holdback	
<input type="checkbox"/>	0.50	<input type="checkbox"/>	37.40	<input type="checkbox"/>	240	<input type="checkbox"/>	1/4 inch		
<input type="checkbox"/>	0.75	<input type="checkbox"/>	39.37	<input type="checkbox"/>	300	<input type="checkbox"/>	5/16 inch	<input type="checkbox"/> mech. backstop, clockwise <input type="checkbox"/> mech. backstop, counterclockwise <input type="checkbox"/> internal brake <input type="checkbox"/> external brake shaft	
<input type="checkbox"/>	1.0	<input type="checkbox"/>	41.34	<input type="checkbox"/>	384	<input type="checkbox"/>	3/8 inch		
<input type="checkbox"/>	1.5	<input type="checkbox"/>	43.31	<input type="checkbox"/>	480	<input type="checkbox"/>	1/2 inch	Type of Seals	
<input type="checkbox"/>	2.0	<input type="checkbox"/>	45.28	<input type="checkbox"/>	600	Power Cord (if applicable)			
<input type="checkbox"/>	3.0	<input type="checkbox"/>	47.24	<input type="checkbox"/>	768			<input type="checkbox"/>	standard box, standard paint
<input type="checkbox"/>	4.0	<input type="checkbox"/>	49.21	<input type="checkbox"/>	960	<input type="checkbox"/>	standard box, food grade paint		
<input type="checkbox"/>	5.5	<input type="checkbox"/>	51.18	<input type="checkbox"/>	1064	<input type="checkbox"/>	standard box, unpainted	Material & Surface Finish	
<input type="checkbox"/>	7.5	<input type="checkbox"/>	53.15	<input type="checkbox"/>	1320	<input type="checkbox"/>	compact box, unpainted		
<input type="checkbox"/>	10	<input type="checkbox"/>	55.12	Voltage		<input type="checkbox"/>	compact box, stainless steel	<input type="checkbox"/> mild steel, standard paint <input type="checkbox"/> total stainless steel <input type="checkbox"/> semi-rust free	
<input type="checkbox"/>	15	<input type="checkbox"/>	57.09			<input type="checkbox"/>	208v		
<input type="checkbox"/>	20	<input type="checkbox"/>	59.06	<input type="checkbox"/>	230v	<input type="checkbox"/>	power cord, stan. straight connector	Other Special Options	
<input type="checkbox"/>	25	<input type="checkbox"/>	61.02	<input type="checkbox"/>	380v	<input type="checkbox"/>	power cord, SS straight connector		
<input type="checkbox"/>	30	<input type="checkbox"/>	62.99	Phase & Frequency		<input type="checkbox"/>	4 ft, standard insulation	<input type="checkbox"/>	vertical shaft (see page 91)
<input type="checkbox"/>	40	<input type="checkbox"/>	64.96			<input type="checkbox"/>	460v	<input type="checkbox"/>	4 ft, screened
<input type="checkbox"/>	50	<input type="checkbox"/>	66.93	<input type="checkbox"/>	575v	<input type="checkbox"/>	10 ft, standard insulation	<input type="checkbox"/>	CSA approved motor
<input type="checkbox"/>	61	<input type="checkbox"/>	68.90	<input type="checkbox"/>	3ph/60Hz	<input type="checkbox"/>	10 ft, screened	<input type="checkbox"/>	dust explosion proof (per ATEX 95, Zone 22)
<input type="checkbox"/>	75	<input type="checkbox"/>	70.87	<input type="checkbox"/>	3ph/50Hz	Quantity _____ Motorized Pulley(s) Special Comments: _____ _____ _____			
<input type="checkbox"/>	100	<input type="checkbox"/>	72.83	<input type="checkbox"/>	1ph/60Hz				
<input type="checkbox"/>	122	<input type="checkbox"/>	74.80	<input type="checkbox"/>	1ph/50Hz				
<input type="checkbox"/>	150	<input type="checkbox"/>	76.77						
<input type="checkbox"/>	180	<input type="checkbox"/>	78.74						
<input type="checkbox"/>	220	<input type="checkbox"/>	80.71						
<input type="checkbox"/>	270	<input type="checkbox"/>	82.68						
<input type="checkbox"/>	330	<input type="checkbox"/>	84.65						
<input type="checkbox"/>		<input type="checkbox"/>	Other						

* Note that this form displays all powers, speeds, and options available from Rulmeca. Some combinations are unavailable (e.g. 100 HP is not available in 12.64" diameter.)