

## **International Protection (IP) Ratings**

## Protection against solid bodies

IP	Symbol	Test Definition
0		Not Protected
1	ø 525 mm	Protected against touch with the flat of the hand and large solid objects greater than 50mm
2	ø 125mm	Protected against finger-touch and solid objects greater than 12mm.
3	ø 25mm	Protected against solid objects greater than 2.5mm
4	ø 1 mm	Protected against solid objects greater than 1.0mm.
5		Dust-protected Dust shall not penetrate in a quantity to interfere with the satisfactory operation of the apparatus.
6		Dust-tight

Protection of internal equipment against harmful ingress of water		
IP	Symbol	Test Definition
0		Not Protected
1		Protected against dripping water.
2		Protected against dripping water when tilted up 15°.
3		Protected against spraying water.
4		Protected against splashing water.
5		Protected against water jets (P1 nozzle 6.3mm, water delivery rate 12.5 l/min ± 5%)
6		Protected from projections of water similar to marine swells (P2 nozzle 12.5mm, water delivery rate 100 l/min ± 5%)
7	min ols m	Ingress of water in quantities causing harmful effects shall not be possible when the enclosure is temporarily (30 min.) immersed 1 meter in water under standardized conditions of pressure and time
		Ingress of water in quantities causing



Ingress of water in quantities causing harmful effects shall not be possible when the enclosure is continuously immersed in water under conditions which shall be agreed between manufacturer and the user, but are more severe than for no. 7

Protected from four, 30 second, 1,500 psi, spray tests, each at 4" to 6", at 180° F, at 4 gpm, at four different angles