



## Motorized Pulley 80LP

Ø 3.37 in. (80 mm), planetary polymer gearbox

### Product description

Due to its strength, reliability, and need for no maintenance, this Motorized Pulley is used in small conveyors, packaging machines, and simple transfer units.

### Characteristics

- Asynchronous 3 phase or 1 phase AC induction motor
- Integral motor protection
- Planetary gearbox in polymer or polymer / steel combination
- Low noise operation
- Light and distributed weight
- Maintenance free
- Lifetime lubrication
- Reversible operation
- Motorized Pulleys with RL greater than 21.65 inches have reinforced shaft

### Applications

- Small conveyors for light loads, non-continuous use
- Transfer conveyors
- Packaging machines for light loads
- Metal detection, x-ray scanners
- Check stands in supermarkets
- Dry or humid applications

### Technical data

<b>Type of motor</b>	Asynchronous squirrel-cage, IEC 34 (VDE 0530)
<b>Insulation class of motor windings</b>	Class F, IEC 34 (VDE 0530)
<b>Available power supplies*</b>	115v/1ph/60Hz, 230v/1ph/60Hz, 230v/3ph/60Hz, 460v/3ph/60Hz
<b>Seal protection rating</b>	IP66
<b>Thermal protection</b>	Bimetallic contact
<b>Allowable ambient temp., 3-ph motor</b>	+41°F to + 104°F
<b>Allowable ambient temp., 1-phase motor</b>	+50° F to +104° F
<b>Max. roller length (RL)</b>	35.91 in

\* Other power supply voltages and frequencies are available.

