



**Ordering\* Information:  
Rulmeca Drum Motors**

**Email: sales-us@rulmeca.com  
Fax: 910-794-9296**

**Contact Person** \_\_\_\_\_ **Date** \_\_\_\_\_ **Ref#** \_\_\_\_\_  
**Company** \_\_\_\_\_  
**Address** \_\_\_\_\_  
**Phone** \_\_\_\_\_ **Fax** \_\_\_\_\_ **Email** \_\_\_\_\_

Diameter (in)		Roller Length (in)		Belt Speed (fpm)		Lagging Material		Type of Mounting Brackets	
<input type="checkbox"/>	3.15	<input type="checkbox"/>	11.81	<input type="checkbox"/>	10	<input type="checkbox"/>	Blue rubber	<input type="checkbox"/>	aluminum
<input type="checkbox"/>	4.50	<input type="checkbox"/>	12.60	<input type="checkbox"/>	12	<input type="checkbox"/>	White rubber	<input type="checkbox"/>	stainless steel
<input type="checkbox"/>	5.45	<input type="checkbox"/>	13.78	<input type="checkbox"/>	14	<input type="checkbox"/>	Black rubber	<input type="checkbox"/>	cast iron
<input type="checkbox"/>	6.49	<input type="checkbox"/>	15.75	<input type="checkbox"/>	16	<input type="checkbox"/>	None	<b>Type of Holdback</b>	
<b>Power (HP)</b>		<input type="checkbox"/>	17.72	<input type="checkbox"/>	18	<b>Lagging Profile</b>		<input type="checkbox"/>	mech. backstop, clockwise
<input type="checkbox"/>	0.03	<input type="checkbox"/>	19.69	<input type="checkbox"/>	20	<input type="checkbox"/>	Smooth	<input type="checkbox"/>	mech. backstop, counterclockwise
<input type="checkbox"/>	0.05	<input type="checkbox"/>	21.65	<input type="checkbox"/>	24	<input type="checkbox"/>	Profiled	<input type="checkbox"/>	internal brake
<input type="checkbox"/>	0.08	<input type="checkbox"/>	23.62	<input type="checkbox"/>	26	<b>Lagging Thickness</b>		<b>Type of Seals</b>	
<input type="checkbox"/>	0.09	<input type="checkbox"/>	25.59	<input type="checkbox"/>	30	<input type="checkbox"/>	1/8 inch	<input type="checkbox"/>	standard
<input type="checkbox"/>	0.10	<input type="checkbox"/>	27.56	<input type="checkbox"/>	38	<input type="checkbox"/>	1/4 inch	<input type="checkbox"/>	IP69
<input type="checkbox"/>	0.11	<input type="checkbox"/>	29.53	<input type="checkbox"/>	48	<input type="checkbox"/>	1/2 inch	<input type="checkbox"/>	regreasable
<input type="checkbox"/>	0.12	<input type="checkbox"/>	31.50	<input type="checkbox"/>	60	<b>Termination (select one)</b>		<b>Material &amp; Surface Finish</b>	
<input type="checkbox"/>	0.13	<input type="checkbox"/>	33.46	<input type="checkbox"/>	76	<input type="checkbox"/>	compact box, AL	<input type="checkbox"/>	stan. mild steel & aluminum
<input type="checkbox"/>	0.15	<input type="checkbox"/>	35.43	<input type="checkbox"/>	96	<input type="checkbox"/>	compact box, SS	<input type="checkbox"/>	total stainless steel
<input type="checkbox"/>	0.16	<input type="checkbox"/>	37.40	<input type="checkbox"/>	120	<input type="checkbox"/>	power cord, elbow	<input type="checkbox"/>	semi-rust free
<input type="checkbox"/>	0.20	<input type="checkbox"/>	39.37	<input type="checkbox"/>	150	<input type="checkbox"/>	power cord, straight	<b>Other Special Options</b>	
<input type="checkbox"/>	0.24	<input type="checkbox"/>	41.34	<input type="checkbox"/>	192	<b>Power cord (if applicable)</b>		<input type="checkbox"/>	vertical shaft
<input type="checkbox"/>	0.25	<input type="checkbox"/>	43.31	<input type="checkbox"/>	240	<input type="checkbox"/>	10 ft, standard insulation	<input type="checkbox"/>	inclined shaft
<input type="checkbox"/>	0.33	<input type="checkbox"/>	45.28	<input type="checkbox"/>	300	<input type="checkbox"/>	10 ft, screened	<input type="checkbox"/>	encoder (SKF)
<input type="checkbox"/>	0.40	<input type="checkbox"/>	47.24	<input type="checkbox"/>	384	<b>Type of Oil</b>		<input type="checkbox"/>	encoder (RLS)
<input type="checkbox"/>	0.50	<input type="checkbox"/>	49.21	<input type="checkbox"/>	480	<input type="checkbox"/>	mineral	<input type="checkbox"/>	low noise
<input type="checkbox"/>	0.75	<input type="checkbox"/>	51.18	<input type="checkbox"/>	600	<input type="checkbox"/>	synthetic	<input type="checkbox"/>	special certification (please specify)
<input type="checkbox"/>	1.00	<input type="checkbox"/>	53.15	<input type="checkbox"/>	768	<input type="checkbox"/>	food grade	<input type="checkbox"/>	special shell (attach drawing)
<input type="checkbox"/>	1.33	<input type="checkbox"/>	55.12	<b>Voltage</b>		<b>Motor Insulation</b>		<input type="checkbox"/>	special end housing (attach drawing)
<input type="checkbox"/>	1.50	<input type="checkbox"/>	57.09	<input type="checkbox"/>	115v	<input type="checkbox"/>	class F	<input type="checkbox"/>	special shaft (attach drawing)
<input type="checkbox"/>	2.00	<input type="checkbox"/>	59.06	<input type="checkbox"/>	208v	<input type="checkbox"/>	class H	<input type="checkbox"/>	special key requirements (attach
<input type="checkbox"/>	3.00	<input type="checkbox"/>	61.02	<input type="checkbox"/>	230v	<b>Type of Crown</b>		<b>Center Groove Dimensions (if applicable)</b>	
		<input type="checkbox"/>	62.99	<input type="checkbox"/>	240v	<input type="checkbox"/>	center crown	Top	_____ (in.)
		<input type="checkbox"/>	64.96	<input type="checkbox"/>	380v	<input type="checkbox"/>	trapezoidal crown	Bottom	_____ (in.)
		<input type="checkbox"/>	66.93	<input type="checkbox"/>	460v	<input type="checkbox"/>	no crown	Depth	_____ (in.)
		<input type="checkbox"/>	68.90	<input type="checkbox"/>	575v				
		<input type="checkbox"/>	70.87	<b>Phase &amp; Frequency</b>					
		<input type="checkbox"/>	72.83	<input type="checkbox"/>	3ph/60Hz				
		<input type="checkbox"/>	74.80	<input type="checkbox"/>	3ph/50Hz				
		<input type="checkbox"/>	76.77	<input type="checkbox"/>	1ph/60Hz				
		<input type="checkbox"/>	78.74	<input type="checkbox"/>	1ph/50Hz				
		<input type="checkbox"/>	Other	<input type="checkbox"/>	Other				

**Quantity:** \_\_\_\_\_ **Drum Motors**  
**Special Comments:** \_\_\_\_\_

\* Note: This form displays all powers, speeds, and options available in small drum motors from Rulmeca. Some combinations are unavailable (e.g. 3 HP is not available in 4.5 inch diameter).